

## Texxon AW 68 Hydraulic Fluid

**Description:** These products are high quality anti-wear hydraulic oils containing anti-oxidant, anti-corrosion and anti-foam additives. They have very good stability and demulsibility properties and meet the requirements of major hydraulic pump and equipment manufacturers.

**Recommendations:** These hydraulics oils are suitable for all hydraulic fluid power transmission systems subjected to severe duty. They are recommended for critical hydraulic systems, which must remain operational, where the cost of downtime and maintenance are high, or where long service intervals are required.

**Characteristics:**

Viscosity @ 40 °C cSt 68

Viscosity @ 100 °C cSt 8.7

Density @ 15 °C kg/L 0.888

Flash Point °C >220

**Performance** Vickers V-104C and 35VQ25 vane, 1-286-S, M2950-S; Denison

**Requirements:** HF-1, HF-2, HF-0; Racine, variable volume vane pumps; Cincinnati Milacron, P-68, P-69, P-70; DIN 51524 Part 2, Lee-Norse 100-1; Jeffrey No. 87; Ford M-6C32, US Steel 136, 127; BF Goodrich 0152; General Motors LH-04-1, LH-06-1, LH-15-1; Commercial Hydraulics (except PM500 Series) AFNOR E48-603.

